| REV. | DATE | DESCRIPTION |
|---|---|---|
| A | 05/01/04 | UPDATE DRAWING FORMAT |







RECOMMENDED CABLE
STRIPPING DIM'S.

NOTE:

1. CONTACT PIN TO SOLDER

| | | | | |
|---|---|---|---|---|
| 8 | | | | |
| 7 | | | | |
| 6 | COVER | BRASS | GOLD | 1 |
| 5 | INSULATOR | TEFLON | NATURAL | 1 |
| 4 | RETAINER RING | BER. COPPER | GOLD | 1 |
| 3 | CONTACT PIN | BRASS | GOLD | 1 |
| 2 | INSULATOR | TEFLON | NATURAL | 1 |
| 1 | BODY | BRASS | GOLD | 1 |
| | DESCRIPTION | MATERIAL | FINISH | QTY |

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

| APPROVALS | | DATE |
|---|---|---|
| DRAWN | G.R.S. | 05/01/04 |
| CHECKED | | |
| ISSUED | | |
| SHEET | 1 OF 1 | |

CAD FILE C:/262/262113.DWG

Amphenol Connex

PART DESCRIPTION
MMCX R/A SEMI-RIGID PLUG
(FOR .085", .086")

PART NO. 262113

DWG. NO. 262113.DWG | REV. A | SIZE A | SCALE NA