

SENCITY® Omni-M dual-band WiFi Stick Antenna 1355.17.0003

SOA-2455/360/6/0/V

Description

Omni-directional dual-band WiFi stick antenna
 IEEE 802.11 b/g/a/h/p for 2.3 - 2.5 GHz and 4.8 to 6 GHz
 WiFi wireless LAN / WLAN
 Gain 6 dBi, vertical polarized antenna
 Ingress protection IP 67 (IEC 60529)
 For outdoor and indoor applications

*** Wall- or pole mount with L-bracket ***



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2	Band 3
Frequency (MHz)	2300 - 2500	4800 - 5150	5150 - 6000
VSWR	1.5	1.7	1.7
Impedance (Ohm)	50	50	50
Gain (dBi)	6	5	6
3dB beamwidth (h) (°)	360	360	360
3dB beamwidth (v) (°)	20	12	12

Ports

	Port 1
Connector	N, jack (female)
Polarization	vertical

Connections

	Band 2	Band 3	Band 4
Port 1	X	X	X

General Data

DC Grounding No
 Composite Power max (W) 25

Mechanical Data

Dimensions (mm) 240 x 25 (Height x Diameter)
 Weight (kg) 0.3

INCLUDED MOUNTING MATERIAL: Bracket 9091.99.0173 and 2 metal-bands for mast-diameter 25mm - 101mm, all piece parts made of stainless steel

Environmental Data

Environmental conditions outdoor
 Operation temperature (°C) -40 to 85
 Storage temperature (°C) -55 to 85
 Transport temperature (°C) -40 to 85
 IP rating IP67
 Flammability rating UL 94-HB
 RoHS 2011/65/EU compliant
 Lead-free soldered yes
 REACH 2006/1907/EC compliant

SENCITY® Omni-M dual-band WiFi Stick Antenna 1355.17.0003

LOW TEMPERATURE: IEC 60068-2-1 72h -55°C
HIGH TEMPERATURE: IEC 60068-2-2 72h +85°C
HUMIDITY: ETSI EN300-2-4 T4, 1E 144h 95%
SALT SPRAY: EN 60068-2-11 / GB-T 10125 96h
MECHANICAL SHOCK: IEC 60721-3-4, 4M5
VIBRATION: IEC 60721-3-4 30 min/axis random 4M5

Material Data

Radome colour	RAL 9003 (signal white)
Radome material	Glass Fibre

Related Products

9091.99.0173 L - bracket for omni stick antennas

Related Documents

Mounting instruction	DOC-0000296554
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00298652
3D-model	DOC-0000715586