

SENCITY® Spot-S WiFi Antenna 1324.17.0098

SPA-2400/75/9/0/V_4

Description

Directional, planar, linear vertical polarized WiFi antenna with 8.5 dBi gain
 WLAN IEEE 802.11 b/g - WiFi band 2.4 - 2.485 GHz
 Approved acc. to EN 50155 (2007) and EN 45545-2 (2012) for railway rolling stock
 and EN 50125-3 (2003) for railway signalling and telecommunications on track-side
 For outdoor and indoor applications
 Ingress protection IP 66 and IP 67

Wall mounting material included



Product Configuration

Technical Data

Electrical Data

	Band 1
Frequency (MHz)	2400 - 2500
VSWR	1.5
Impedance (Ohm)	50
Gain (dBi)	8.5
3dB beamwidth (h) (°)	75
3dB beamwidth (v) (°)	75
Front to back ratio (dB)	12
Vertical electrical tilt (°)	0

Ports

	Port 1
Connector	N, jack (female)
Polarization	vertical

General Data

DC Grounding	Yes
Composite Power max (W)	10

- Meets EN 50155 railway standard fire retardant acc. to DIN 5510-2, EN 45545-2, BS 6853, and outdoor use acc. to NF F16-101/102
- Meets environmental standards according to EN 60068

Mechanical Data

Dimensions (mm)	101 x 81 x 36 (Height x Width x Depth)
Weight (kg)	0.11
Windload	frontal: 15 N at 160 km/h , Wind speed survival: 220 km/h
Included mounting material	Wall mounting material

Environmental Data

Environmental conditions	outdoor
Operation temperature (°C)	-40 to 85
Storage temperature (°C)	-40 to 85
Transport temperature (°C)	-40 to 85
Flammability rating	EN 45545-2
RoHS 2011/65/EU	compliant
Lead-free soldered	yes
REACH 2006/1907/EC	compliant

IP RATING: IP 66 / IP 67 (IEC 60529)

SOLAR RADIATION: EN 50125-3:2004 §4.9, 1120 W/m² for 20h

SENCITY® Spot-S WiFi Antenna 1324.17.0098

AIR PRESSURE: EN 50125-3:2004 §4.2, Altitude Class A1 (up to 1400m)
AIR PULE PRESSURE: EN 50125-3:2004 §4.2, 1 kPa/s
RAIN: EN 50125-3:2004 §4.6, delivery rate: 6 mm/min
VIBRATION / SHOCK: EN 50125-3:2004 §4.13, position profile: "outside the track"
POLLUTION: EN 50125-3:2004 §4.11, pollution levels: 4B1, 4S1
CORROSION: MIL-F-14072 E Type 1 "exposed"
MECHANICAL IMPACT (HAMMER IMPACT): EN 60068-2-75 (IEC 62262/2002-02 IK06)

Material Data

Radome colour	RAL 7044 (grey)
Radome material	PC (Polycarbonate)

Related Products

9091.99.0238 Down_Sidetilt Bracket_SencitySpot-S outdoor
9091.99.0237 L-Bracket for SPOT-S antennas

Related Documents

Mounting instruction	DOC-0000287053
Painting instruction	DOC-0000197967
Security instruction	DOC-0000278984
Outline drawing	DOU-00135740
3D-model	DOC-0000344274

Additional Information

Following Declaration of Conformity for SENCITY® Spot-S antennas are available on request:

- * Industrial standards EN 60068 / EN 60529 / IEC 61373 s ref. DOC-0000318049
- * Railway rolling stock, environmental standards EN 50155 and fire behaviour EN 45545-2 ref. DOC-0000380375
- * Railway trackside, environmental standards EN 50125-3 and fire behaviour EN 45545-2 ref. DOC-0000411396