


## Flexible microwave cable EACON\_6C

### Description

Eacon: Field mountable flexible microwave cables  
 50 Ohm, 18 GHz, 200°C, ø7.7 mm, FEP jacket



### Technical Data

#### Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Wire	2.05 mm
Dielectric	PTFE-LD		6.2 mm
Outer conductor	Copper, Silver plated	wrapped Foil, 100%	6.42 mm
Outer conductor	Copper, Silver plated	Braid	7.1 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 9010 - wh	7.7 mm +/- 0.1

#### Electrical Data

Impedance	50 Ω +/- 1
Operating Frequency	18 GHz
Capacitance	87 pF/m
Velocity of signal propagation	77 %
Signal delay	4.3 ns/m
Screening effectiveness	≥ 90 dB (up to 18 GHz)
Operating voltage	≤ 3.8 kV <sub>rms</sub> (at sea level)

#### Mechanical Data

Weight	14.8 kg/100 m
Min. bending radius	static repeated dynamic
	24 mm
	40 mm

#### Environmental Data

Temperature range	-55 °C ... +200 °C
Flame propagation test	MIL-T-87104 § 4.6.4.8, , FAR 25.869
Halogen free	No
2011/65/EU (RoHS)	compliant
2006/1907/EC (REACH)	compliant
2000/53/EC (ELV)	compliant
2012/19/EU (WEEE)	no special marking needed

### Additional Information

#### Ordering Information

Order as EACON\_6C

#### Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

#### Suitable Connectors

Cable group U96 EACON\_6C

## Flexible microwave cable EACON\_6C

**Matrix** typical Attenuation [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] and maximum Power CW [ formula:  $(p/f^{0.5})$  ]

Coefficients:

a = 0.15

b = 0.0071

$f_{\max} = 18$

P at 1GHz = 1582

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,9	0,15	0,045	1668
1,8	0,21	0,065	1179
2,7	0,27	0,081	963
3,6	0,31	0,095	834
4,5	0,35	0,107	746
5,4	0,39	0,118	681
6,3	0,42	0,128	630
7,2	0,45	0,138	590
8,1	0,48	0,148	556
9,0	0,51	0,157	527
9,9	0,54	0,165	503
10,8	0,57	0,174	481
11,7	0,6	0,182	463
12,6	0,62	0,190	446
13,5	0,65	0,197	431
14,4	0,67	0,205	417
15,3	0,7	0,212	404
16,2	0,72	0,219	393
17,1	0,74	0,226	383
18,0	0,76	0,233	373