

For more Information  
please call

1-800-Belden1



## Description:

RG-58A/U type, 20 AWG stranded (19x32) .037" tinned copper conductor, foam polyethylene insulation, tinned copper braid shield (96% coverage), PVC jacket.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	19x32	TC - Tinned Copper	0.9398

### Insulation

#### Insulation Material:

Insulation Material	Dia. (mm)
FPE - Foam Polyethylene	2.8956

### Outer Shield

#### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	TC - Tinned Copper	93

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

### Overall Cabling

Overall Nominal Diameter: 4.928 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +80°C
UL Temperature Rating:	80°C (UL AWM Style 1354)
Bulk Cable Weight:	37.205 Kg/Km
Max. Recommended Pulling Tension:	222.410 N
Min. Bend Radius (Install)/Minor Axis:	50.800 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 1354 (30 V 80°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes

EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
PMSHA Specification:	SC-182/5
RG Type:	58A/U

### Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black jacket only
Suitability - Aerial:	Yes - Black jacket only - when supported by a messenger wire

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
54

### Nom. Inductance:

Inductance ( $\mu\text{H}/\text{m}$ )
0.213265

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
86.9465

### Nominal Velocity of Propagation:

VP (%)
73

### Nominal Delay:

Delay (ns/m)
4.56059

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
28.8728

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
13.4521

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	1.3124
10	4.2653
50	10.1711
100	14.7645
200	21.6546
400	32.81
700	46.5902
900	54.4646
1000	59.3861

### Max. Operating Voltage - UL:

Voltage
30 V RMS (UL AWM Style 1354)
300 V RMS (CM)

Other Electrical Characteristic 1: Actual Impedance specification is 53.5 +/- 3 ohms.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8219 009U500	152 MT	6.124 KG	WHITE		RG58A/U TYPE COAX
8219 0091000	305 MT	11.793 KG	WHITE	C	RG58A/U TYPE COAX
8219 010U1000	305 MT	12.247 KG	BLACK		RG58A/U TYPE COAX
8219 010U500	152 MT	6.350 KG	BLACK		RG58A/U TYPE COAX
8219 0101000	305 MT	11.793 KG	BLACK	C	RG58A/U TYPE COAX
8219 010500	152 MT	5.897 KG	BLACK	C	RG58A/U TYPE COAX

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 09-23-2008

© 2011 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.