

Coaxial Panel Connector 22_MM CX-50-0-4/111_O

Description

Straight bulkhead receptacle jack

Interface standards
SUHNER-MM CX



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 6 GHz |

Mechanical Data

| | |
|-------------------|-----------|
| Chassis torque | 0.4 Nm |
| Number of matings | 500 |
| Weight | 0.0003 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -55 °C to 155 °C |
| 2011/65/EU, RoHS | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | Gold Plating (without Nickel underplating) |
| Body | Brass | Gold Plating (without Nickel underplating) |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00010462 |
| Catalogue drawing | DCA-00010464 |
| Mounting hole | DOU-00009144 |

Ordering Information

| | |
|----------------------|------------------------|
| Bulk 100 pcs package | 22_MM CX-50-0-4/111_OH |
|----------------------|------------------------|