


- 1.0 PERFORMANCE
 1.1 FREQUENCY RANGE: SEE TABLE
 1.2 VOLTAGE RATING: 1000V RMS (sea level)
 1.3 NOMINAL IMPEDANCE: 50 OHMS
 1.4 DWV: 2500V RMS @ 60Hz (sea level)
 1.5 TEMPERATURE RANGE: -65°C TO +165°C
 2.0 MATERIALS
 2.1 DIELECTRIC: TEFLON, ASTM-D-1710
 2.2 CENTER CONTACT: BeCu, ASTM-B-196

- 2.5 ALL OTHER METAL PARTS: BRASS, ASTM-B-16
 3.0 FINISHES
 3.1 CENTER CONTACT: SEE TABLE
 3.2 ALL OTHER METAL PARTS: SEE TABLE
 4.0 MECHANICAL
 4.1 INTERFACE IN ACCORDANCE WITH MIL-STD-348

DWG NO. OL-0406-214-1 REV. B

PLATING VARIATIONS			
PART NUMBER	FREQUENCY RANGE	BODY	CONTACT
0406-214	DC-11 GHz	NICKEL	SILVER
0406-214 AL/SI	DC-11 GHz	ALBALOY	SILVER
0406-214-NG	DC-11 GHz	NICKEL	GOLD
0406-214-HF-NG	DC-18 GHz	NICKEL	GOLD
0406-214-AG	DC-11 GHz	ALBALOY	GOLD


DO NOT SCALE DRAWING



Rev.	Revisions	Disp.	Date	Dwn.	Appd.
B	ADD PLT. CHART & FREQ. RANGE	NEW	12/30/04	RF	FSH
A	ORIGINAL	NEW	1/25/02		
Ref.:	REMOVE ALL BURRS AND SHARP EDGES .005 MAX.	INTERPRET PER ASME Y14.5M-1994			

THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO SAN-TRON INC. IT MUST NOT BE REPRODUCED OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED IN WRITING BY SAN-TRON INCORPORATED.

UNLESS OTHERWISE SPECIFIED:
 ALL DIMENSIONS ARE IN INCHES.
 ALL DIMENSIONS ARE AFTER PLATING.
 .XXX= ±.005 ALL MACHINED SURFACES 63/ MAX.
 .XX= ±.01 ANG.±1/2° FRACTIONAL= ±1/64
 .004 MAX. TIR.



THIRD ANGLE PROJECTION

DWN	JMB	1/22/02
CHKD	SJS	1/24/02
APPR	JO	2/11/02



SAN-TRON, INC.
 4 NEWBURYPORT TPK. IPSWICH MA USA 01938
 TEL: 978 - 356 -1585 FAX: 978 - 356 -1573
 WWW. santron.com E MAIL: santron@santron.com

TITLE N PANEL RECEPTACLE STRAIGHT .69 FLANGE, EXTENDED POST, (HIGH FREQUENCY)

MATERIAL: SEE NOTE 2.0 FINISH: SEE NOTE 3.0

CAGE CODE: 50896 DWG NO. OL-0406-214-1 REV. B
 SCALE X:X