P/N	APPLICABLE NOTES
-2CC	1,2

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	BY
–	–	–	–	–





DRAWING NO.	REV.
5225	–

NOTE(S):

1. MATERIALS:
   - 1.1 BODY: 303 SST PER ASTM A-582.
   - 1.2 INSULATOR: PTFE PER ASTM D-1710
   - 1.3 CENTER CONDUCTOR: BeCu ALLOY C173 PER ASTM B-196.
   - 1.4 EPOXY: SIGMA VF TYPE HV

2. FINISH(ES):
   - 2.1 BODY AND CENTER CONDUCTOR : GOLD PLATED PER ASTM B-488 OVER NICKEL PLATED PER AMS-QQ-N-290.
   - 2.2 INSULATOR AND GASKET: NONE

NOTICE

THIS DRAWING EMBODIES A CONFIDENTIAL PROPRIETARY DESIGN ORIGINATED BY TENSOLITE COMPANY AND ALL DESIGN, MANUFACTURING REPRODUCTION, USE AND SALE RIGHTS REGARDING THE SAME ARE EXPRESSLY RESERVED. IT IS SUBMITTED UNDER A CONFIDENTIAL RELATIONSHIP FOR A SPECIFIED PURPOSE AND THE RECIPIENT AGREES BY ACCEPTING THIS DRAWING NOT TO SUPPLY OR DISCLOSE ANY INFORMATION REGARDING IT TO ANY UNAUTHORIZED PERSON TO INCORPORATE IN OTHER PROJECTS ANY SPECIAL FEATURES PECULIAR TO THIS DESIGN. ALL PATENT RIGHTS HERETO ARE EXPRESSLY RESERVED BY TENSOLITE COMPANY, LONG BEACH, CALIFORNIA 90815.

TOLERANCES AND NOTES EXCEPT AS NOTED

DIMENSIONS ARE IN INCHES.
LINEAR .XX ±.015, .XXX ±.005 ANGULAR ± 1/2"
FRACTION ± 1/32

1. MACHINE FINISH: 63 RMS
2. BREAK ALL SHARP EDGES .003 MAX.
3. MACHINED FILLETS .005 MAX.
4. MACHINED SURFACES SQUARE TO RESPECTIVE AXIS WITHIN .005 INCHES PER INCH.
5. MACHINED DIAMETERS CONCENTRIC WITHIN .002 T.I.R.
6. DIMENSIONS TO BE MET BEFORE PLATING.
7. CHAMFER ALL THREADS 45°.
8. THREADS PER H-28
9. REMOVE FRAYED EDGES ON TEFLON.
10. REMOVE ALL BURRS.

SEE NOTES	–	SEE NOTES	–
MATERIAL	SIZE	SPECIFICATION	PROCUREMENT

NEXT ASSY

APPROVAL INITIALS		DATE
DRAWN BY	IMG	03/14/02
CHECKED	AGS	08.08.02
QUALITY		
ENGINEERING	ATV	11.25.02

Tensolite
HIGH PERFORMANCE CABLES & INTERCONNECT SYSTEMS
Long Beach, California 90815

TITLE SMA FEMALE 2 HOLE FLANGE (.223 X .625) MOUNT TO Ø .085 SEMI-RIGID CABLE

SCALE	SUB-DIRECTORY\FILENAME	SHEET	REV.
10/1	OL_	1 OF 1	–

SIZE	CAGE CODE	DRAWING NO.
C	30990	5225