

RF Attenuator 5903.17.0005

Description

Standard Attenuator, Medium Power



Product Configuration

Connector (side 1 / side 2) N plug (male) / N jack (female)
 Interface Standards IEC 60169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Nominal impedance 50 Ω
 Nominal attenuation 3 dB
 Frequency range DC to 6 GHz
 Frequency sub range (GHz) DC to 2 2 to 6
 Attenuation deviation (±dB) 0.2 0.3
 VSWR max. 1.1 1.25
 Power rating 50 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.
 Convection cooled.
 500 Watt peak power, 5 μs pulse, 0.05 % duty cycle

Mechanical Data

Weight 0.485 kg

Environmental Data

Operating temperature -55 °C to 130 °C
 2011/65/EC (RoHS) compliant

Material Data

Piece Part (side 1)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Piece Part (side2)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00005339

Ordering Information

Single packaging 5903.17.0005

Important note WARNING Beryllia Ceramic Inside! DO NOT sand, scrap or tamper with. Dispose in accordance with all relevant regulations.

RF Attenuator 5903.17.0005