

INTERFACE DESIGN STANDARD		<i>The PHOENIX Company of Chicago, Inc.</i> 22 GREAT HILL RD., NAUGATUCK, CT 06770 WWW.PHOENIXOFCHICAGO.COM PHONE: (800) 323-9562	REV.	DESCRIPTION	BY	DATE	APPR.	DATE
IDS-268			E	PER ECN 13033	ST	07/24/2018	JEM	07/24/2018
SHEET 1 OF 3			F	PER ECN 13488	CA	09/10/19	JEM	09/10/19
DATE: 06/01/17	APPROVED: RMB		G	PER ECN 13787	BGW	06/18/2020	RMB	06/18/2020
DRAWN: JEM			H	PER ECN 14401	SPS	05/22/2024	SJG	05/22/2024

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.

268 SERIES, SIZE 16 PkZ® FOR ARINC 600 CONNECTOR HOUSINGS, 50 OHMS, 50 GHz FREQUENCY

MATERIALS

BODIES: BRASS PER ASTM B16.
INSULATORS: TEFLON (PTFE) PER ASTM D1710.
CENTER AND OUTER CONTACTS: BERYLLIUM COPPER
PER ASTM B196.

PLATING

GOLD PER MIL-DTL-45204 (ELECTRO DEPOSITED).
COPPER PER SAE AMS2418 (ELECTRO DEPOSITED).
NICKEL PER QQ-N-290.

FINISH (ADD LETTER TO END OF PART NUMBER)

BODIES AND CENTER CONTACTS:
- "A": .000050 MIN. GOLD OVER NICKEL.
- "C": .000050 MIN. GOLD OVER COPPER.
OTHER METAL PARTS: PLATED TO MEET THE
ENVIRONMENTAL REQUIREMENTS.

MATING CHARACTERISTICS

OUTER BODIES:
- INSERTION - 24 oz. (1.5 lbs) MAX.
- WITHDRAWAL - 2 oz. (.125 lbs) MIN.
CENTER CONTACTS:
- INSERTION - 14 oz. (.875 lbs) MAX.
- WITHDRAWAL - .5 oz. (.031 lbs) MIN.
HOUSING RETENTION - 192 oz. (12 lbs.) MIN.
AXIAL MATING TOLERANCE - .110 [2.79]

CONFIGURATIONS

HOUSING: ARINC 600 PLUG AND RECEPTACLE CONNECTOR SHELLS, SIZE 16 CAVITY. (REF: MIL-DTL-83527B)
CABLES: RG-178, RG-316, RG-405 OR EQUIVALENT FLEXIBLE CABLES.
INSERTION TOOL: M81969/1-03.
EXTRACTION TOOL: M81969/1-03 OR M81969/8-208.
DESIGN TERMINATION: CRIMP/CLAMP, SOLDER/CLAMP, DIRECT SOLDER, DIRECT CRIMP.
PkZ CONTACTS DO NOT MATE WITH OTHER INDUSTRY-STANDARD SIZE 12 CONTACTS.

ELECTRICAL (CONFIGURATION DEPENDENT)

IMPEDANCE: 50 OHMS.
FREQUENCY RANGE: DC TO 50 GHz.
VOLTAGE RATING STRAIGHT: 700 VRMS.
VOLTAGE RATING ANGLED: 500 VRMS.
INSULATION RESISTANCE: 2000 MEGOHMS MIN.

CONTACT RESISTANCE:
- CENTER CONTACT 6 MILLIOHMS
- OUTER CONTACT 4 MILLIOHMS
VSWR: CONFIGURATION DEPENDENT.
INSERTION LOSS: .06√f(GHz) dB
R.F. LEAKAGE: -90 dB MIN. @ 2-3 GHz.


ENVIRONMENTAL

OPERATING TEMPERATURE: -55°C TO + 165°C
VIBRATION: MIL-STD-202, METHOD 204, TEST CONDITION D.
SHOCK: MIL-STD-202, METHOD 213, TEST CONDITION I.
SALT SPRAY: MIL-STD-1344, METHOD 1001, CONDITION B.
DURABILITY: 500 CYCLES.


THERMAL SHOCK: MIL-STD-202, METHOD 107.
TEST CONDITION B, EXCEPT HIGH
TEMPERATURE SHALL BE+85°C.
MOISTURE RESISTANCE: MIL-STD-202,
METHOD 106.
INSULATION RESISTANCE: 2000 MEGOHMS
POST HUMIDITY.

INTERFACE DESIGN STANDARD		<i>The PHOENIX Company of Chicago, Inc.</i> 22 GREAT HILL RD., NAUGATUCK, CT 06770 WWW.PHOENIXOFCHICAGO.COM PHONE: (800) 323-9562
IDS-268		
SHEET 2 OF 3	DATE: 06/01/17	
DRAWN: JEM	APPROVED: RMB	
WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.		

CONTACTS:




CONTACTS IN CONNECTOR HOUSINGS:



INTERFACE DESIGN STANDARD		<i>The PHOENIX Company of Chicago, Inc.</i> 22 GREAT HILL RD., NAUGATUCK, CT 06770 WWW.PHOENIXOFCHICAGO.COM PHONE: (800) 323-9562
IDS-268		
SHEET 3 OF 3	DATE: 06/01/17	
DRAWN: JEM	APPROVED: RMB	
WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.		

CONTACT MATING IN CONNECTOR HOUSINGS:

HANDLE WITH CARE



CAUTION

- PRECISION CONTACTS WITH SMALL DIAMETERS ARE USED IN THESE CONNECTORS TO ACHIEVE SUPERIOR ELECTRICAL AND MECHANICAL PERFORMANCE.
- CARE IS REQUIRED WHEN MATING THESE CONNECTORS TO PROTECT THE CONTACTS FROM DAMAGE AND ACHIEVE OPTIMAL PERFORMANCE.
- STABILIZING RINGS FOR PKZ PLUG CONTACTS CAN BE USED TO AID IN THE MATING OF THE CONNECTORS.