

PERFORMANCE		MATERIALS (FINISH): FINISHES PER STI 7.3.1-8	
FREQUENCY RANGE	DC - 110 GHz	BODY	SS303 (PASSIVATE)
NOMINAL IMPEDANCE	50 Ω	CONTACT	BeCu (Au/Ni)
DWV @60Hz [SEA LEVEL]	500 Vrms	DIELECTRIC	PEI
VSWR	< 1.35 (DC - 110 GHz)	COUPLING NUT	SS303 (PASSIVATE)
TEMPERATURE RANGE	-40 / +85 °C		

MECHANICAL	
INTERFACES PER	IEEE
CONTACT RETENTION	3 LBs AXIAL
DURABILITY	500 CYCLES

PART NUMBER	
5810-03-PJ	

Description:
Adapter: 1.0mm Female; to 1.0mm Male; Straight

DWG NO. OL-5810-03-1

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES.
ALL DIMENSIONS ARE AFTER PLATING.
.XXX = ±.005 ALL MACHINED SURFACES MAX.
.XX= ±.01 ANG. ±1/2° FRACTIONAL = ± 1/64
[Symbol] .004 MAX TIR. [Symbol] AXIS .001

Projection:
THIRD ANGLE
[Symbol]

SCALE 8:1

4 TURNPIKE ROAD
IPSWICH MA 01938
USA

San-tron
WWW.SANTRON.COM
SANTRON@SANTRON.COM
(978) 356-1585

This drawing and any information or descriptive material set out on it are the confidential and copyright property of SAN-TRON, INC. © and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of SAN-TRON, INC.

CAGE:
50896