

	6	5	4	3	2	1																																																										
F	1.0 PERFORMANCE 1.1 FREQUENCY RANGE: DC-50GHz 1.2 NOMINAL IMPEDANCE: 50 OHMS 1.3 DWV: 325Vrms 1.4 TEMPERATURE RANGE: -55/+165°C		2.0 MATERIALS 2.1 BODY: SS 303, ASTM-A-582 2.2 CONTACT: BeCu, ASTM-B-196 2.3 DIELECTRIC: ULTEM 1000 3.0 FINISHES 3.1 BODY & BUSHING: PASSIVATE PER ASTM-A-967 3.2 CONTACT: GOLD PER ASTM-B488, TYPE I, CODE C, CLASS 1,27		4.0 MECHANICAL 4.1 INTERFACES: MIL-STD-348 4.2 CONTACT RETENTION: N/A 4.3 DURABILITY: 500 CYCLES																																																											
E					DWG NO. OL-4206-04-1 REV. A																																																											
D					PART NUMBER 4206-04-M9-PJ 4206-04-M12-PJ																																																											
C					Ø A .0421 .0483																																																											
B					Ø PIN .009 .012																																																											
A					PLATING PER SAN-TRON SPEC. 7.3.1-8																																																											
<table><tr><td colspan="6">REVISIONS</td><td>Material: SEE NOTES</td><td rowspan="2">This drawing and any information or descriptive material set out on it are the confidential and copyright property of SAN-TRON, INC. © and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of SAN-TRON, INC.</td><td colspan="2" rowspan="2">Description: 2.4mm FIELD REPLACEABLE JACK .550 2H FLANGE</td></tr><tr><td>REV.</td><td>DESCRIPTION</td><td>DISP</td><td>DATE</td><td>ECN</td><td>DRAWN</td><td>APPROVED</td><td>Finish: SEE TABLE</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES. ALL DIMENSIONS ARE AFTER PLATING. .XXX = ±.005 ALL MACHINED SURFACES .XX = ±.01 ANG. ±1/2° FRACTIONAL = 1/64 Ⓢ.004 MAX TIR. Ⓢ.001 MAX. TIR.</td><td colspan="2">Company Confidential</td></tr><tr><td>A1</td><td>REDRAW</td><td>FIFO</td><td>3/14/24</td><td>X</td><td>NBS</td><td>NBS</td><td rowspan="2">Projection Method: THIRD ANGLE REMOVE ALL BURRS AND SHARP EDGES .005 MAX</td><td colspan="2">Legal Owner: SAN-TRON, INC. 4 TURNPIKE ROAD, IPSWICH MA USA 01938 TEL: 978-356-1585 FAX: 978-356-1573 WWW.santron.com EMAIL: santron@santron.com</td></tr><tr><td>A</td><td>RELEASE</td><td>NEW</td><td>04/03/23</td><td>00447</td><td>JL</td><td>JL</td><td>REF:</td><td>CAGE CODE: 50896</td><td>Sheet: 1 of 1</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Approved by: JL</td><td>Approved Date: 10/13/2022</td></tr></table>							REVISIONS						Material: SEE NOTES	This drawing and any information or descriptive material set out on it are the confidential and copyright property of SAN-TRON, INC. © and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of SAN-TRON, INC.	Description: 2.4mm FIELD REPLACEABLE JACK .550 2H FLANGE		REV.	DESCRIPTION	DISP	DATE	ECN	DRAWN	APPROVED	Finish: SEE TABLE								UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES. ALL DIMENSIONS ARE AFTER PLATING. .XXX = ±.005 ALL MACHINED SURFACES .XX = ±.01 ANG. ±1/2° FRACTIONAL = 1/64 Ⓢ.004 MAX TIR. Ⓢ.001 MAX. TIR.	Company Confidential		A1	REDRAW	FIFO	3/14/24	X	NBS	NBS	Projection Method: THIRD ANGLE REMOVE ALL BURRS AND SHARP EDGES .005 MAX	Legal Owner: SAN-TRON, INC. 4 TURNPIKE ROAD, IPSWICH MA USA 01938 TEL: 978-356-1585 FAX: 978-356-1573 WWW.santron.com EMAIL: santron@santron.com		A	RELEASE	NEW	04/03/23	00447	JL	JL	REF:	CAGE CODE: 50896	Sheet: 1 of 1									Approved by: JL	Approved Date: 10/13/2022
REVISIONS						Material: SEE NOTES	This drawing and any information or descriptive material set out on it are the confidential and copyright property of SAN-TRON, INC. © and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of SAN-TRON, INC.	Description: 2.4mm FIELD REPLACEABLE JACK .550 2H FLANGE																																																								
REV.	DESCRIPTION	DISP	DATE	ECN	DRAWN	APPROVED				Finish: SEE TABLE																																																						
							UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES. ALL DIMENSIONS ARE AFTER PLATING. .XXX = ±.005 ALL MACHINED SURFACES .XX = ±.01 ANG. ±1/2° FRACTIONAL = 1/64 Ⓢ.004 MAX TIR. Ⓢ.001 MAX. TIR.	Company Confidential																																																								
A1	REDRAW	FIFO	3/14/24	X	NBS	NBS	Projection Method: THIRD ANGLE REMOVE ALL BURRS AND SHARP EDGES .005 MAX	Legal Owner: SAN-TRON, INC. 4 TURNPIKE ROAD, IPSWICH MA USA 01938 TEL: 978-356-1585 FAX: 978-356-1573 WWW.santron.com EMAIL: santron@santron.com																																																								
A	RELEASE	NEW	04/03/23	00447	JL	JL		REF:	CAGE CODE: 50896	Sheet: 1 of 1																																																						
								Approved by: JL	Approved Date: 10/13/2022																																																							
	6	5	4	3	2	1																																																										