

Coaxial Cable RG_316_/U

Description

PTFE - 50 Ohm - single screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 95%	2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.5 mm +/- 0.1

Print: HUBER+SUHNER RG 316 U 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	3 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.86 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 38 dB (up to 1 GHz)
Max. operating voltage	≤ 1.5 kV _{rms} (at sea level)
Test voltage	3 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.6 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) dynamic
	15 mm 25 mm 37.5 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-3, ,
2011/95/EC (RoHS)	compliant

Additional Information

Ordering Information

Order as RG_316_/U

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group U2 2 mm / 50 Ohm

Coaxial Cable RG_316_/U

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.7727

b = 0.0972

f_{max} = 3

P at 1GHz = 135

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0,15	0,31	0,096	349
0,3	0,45	0,138	246
0,45	0,56	0,171	201
0,6	0,66	0,200	174
0,75	0,74	0,226	156
0,9	0,82	0,250	142
1,05	0,89	0,272	132
1,2	0,96	0,294	123
1,35	1,03	0,314	116
1,5	1,09	0,333	110
1,65	1,15	0,351	105
1,8	1,21	0,369	101
1,95	1,27	0,387	97
2,1	1,32	0,403	93
2,25	1,38	0,420	90
2,4	1,43	0,436	87
2,55	1,48	0,452	85
2,7	1,53	0,467	82
2,85	1,58	0,482	80
3,0	1,63	0,497	78