

Sencity Antenna 1324.26.0002

SPA-2400/70/9/0/RCP

Description

Circular polarised (right-hand) WiMAX, WiFi-Antenna
 IEEE 802.16 (2.3GHz-2.4GHz band), IEEE 802.11 b/g
 Frequency-Band: 2.3GHz-2.5GHz
 BWA, WLAN
 Wall mounting socket included



Product Configuration

Technical Data

Electrical Data

	Band 1
Frequency (MHz)	2300 - 2500
VSWR	1.5
Impedance (Ohm)	50
Gain (dBi)	8.5
3dB beamwidth (h) (°)	70
3dB beamwidth (v) (°)	65
Front to back ratio (dB)	20
Axial ratio (dB)	3
Vertical electrical tilt (°)	0

Ports

	Port 1
Connector	TNC, jack (female)
Polarization	circular right

General Data

DC Grounding	No
Composite Power max (W)	10

Axial Ratio= 3 dB

Mechanical Data

Dimensions (mm)	101 x 95 x 32 (Height x Width x Depth)
Weight (kg)	0.11
Windload	frontal: 15 N at 160 km/h , Wind speed survival: km/h
Included mounting material	Wall mounting material

Mounting socket material: ASA

Mounting socket colour: RAL 7042

Environmental Data

Environmental conditions	indoor
Operation temperature (°C)	-40 to 80
Storage temperature (°C)	-40 to 80
Transport temperature (°C)	-40 to 80
RoHS 2011/65/EC	compliant
REACH 2006/1907/EC	compliant

Sencity Antenna 1324.26.0002

Material Data

Radome colour	RAL 7035 (light-grey)
Radome material	ASA (acrylic ester-styrene-acrylonitrile)
Back plate/base plate colour	RAL 7042 (dark-grey)
Back plate/base plate material	ASA (acrylic ester-styrene-acrylonitrile)

Related Products

9091.99.0029 Pol Bracket
9091.99.0080 Sidetilt Bracket

Related Documents

Mounting instruction	DOC-0000197953
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00018819
3D-model	DOC-0000286562