

## Sencity Antenna 1324.26.0024

SPA-2400/75/8/0/V

### Description

Linear polarised directional WiMAX, WiFi-Antenna  
 IEEE 802.16, IEEE 802.11 b/g  
 Frequency-Band: 2.3GHz-2.8GHz  
 BWA, WLAN  
 Wall and mast mounting material included, supports mast diameter 40mm-60mm



### Product Configuration

#### Technical Data

##### Electrical Data

	Band 1
Frequency (MHz)	2300 - 2800
VSWR	1.5
Impedance (Ohm)	50
Gain (dBi)	7.5
3dB beamwidth (h) (°)	75
3dB beamwidth (v) (°)	70
Front to back ratio (dB)	20
Vertical electrical tilt (°)	0

##### Ports

	Port 1
Connector	TNC, jack (female)
Polarization	vertical

##### General Data

DC Grounding	No
Composite Power max (W)	10

##### Mechanical Data

Dimensions (mm)	101 x 80 x 20 (Height x Width x Depth)
Weight (kg)	0.13
Windload	frontal: 15 N at 160 km/h , Wind speed survival: km/h
Mast diameter (mm)	40 - 60
Included mounting material	Mast mounting material (1 metal band)

##### Environmental Data

Environmental conditions	indoor
Operation temperature (°C)	-40 to 80
Storage temperature (°C)	-40 to 80
Transport temperature (°C)	-40 to 80
RoHS 2011/65/EC	compliant
REACH 2006/1907/EC	compliant

##### Material Data

Radome colour	RAL 7035 (light-grey)
Radome material	ASA (acrylic ester-styrene-acrylonitrile)
Back plate/base plate colour	RAL 7042 (dark-grey)
Back plate/base plate material	ASA (acrylic ester-styrene-acrylonitrile)

## Sencity Antenna 1324.26.0024

### Related Products

9091.99.0191 Wall Bracket

### Related Documents

Mounting instruction	DOC-0000215556
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00018683