


[Home](#) > [Products & Solutions](#) > Microwave USB Power Sensor MA24118A

Microwave USB Power Sensor MA24118A

[Buy on ShopAnritsu](#)

- Products & Solutions
- Services & Support**
- Buy
- About Anritsu
- Contact Us

| | |
|---|--|
|  | <p>Features</p> <ul style="list-style-type: none"> Broad frequency range (10 MHz to 18 GHz) True RMS measurements NIST Traceable calibrations Compatible with Anritsu handhelds Built-in internal and external trigger (only used with PC) High power handling (+33 dBm) 1 mW calibration need eliminated Silicone protective covering for additional field durability Worldwide calibration and service centers |
|---|--|

Description **Specifications** Library

| | |
|--------------------------------------|--|
| Model | MA24118A |
| Frequency Range | 10 MHz to 18 GHz |
| Dynamic Rang | -40 dBm to +20 dBm |
| SWR | <1.17, 10 MHz to 150 MHz <1.12, 150 MHz to 2 GHz <1.22, 2 GHz to 12 GHz <1.25, 12 GHz to 18 GHz |
| Measurement Uncertainty ¹ | <4% |
| RF Connector | N(m) |

Notes: 1) Expanded uncertainty with K=2 for power measurements of a CW signal greater than -20 dBm with zero mismatch errors